

## Setaflex

### Flexible, Rapid Setting Floor & Wall Tile Adhesive

- Flexible, rapid setting formula
- Walk on and grout after 3 hours
- Ideal for plywood & chipboard overlay
- Underfloor Heating
- Natural Stones & Porcelain
- Essential for areas of movement
- Simply mix with water, no additives required



Setaflex is a polymer modified, flexible, cement based floor and wall tile adhesive. Setaflex has been developed for fixing a large variety of tiles to surfaces subject to limited movement and/or vibration such as plywood overlay and underfloor heating. Its rapid setting capability allows for light foot traffic and grouting after 3 hours. Setaflex is suitable for use internally and externally and is unaffected by frost after setting.

Suitable for application to:		Suitable for fixing:
<ul style="list-style-type: none"> <li>• Sand/Cement Screed</li> <li>• Plywood (12mm)</li> <li>• Concrete</li> <li>• Chipboard (18mm)</li> <li>• Gypsum Plaster</li> <li>• Tilebacker Boards</li> <li>• Anhydrite Screeds</li> <li>• Plasterboard</li> <li>• Existing Tiles</li> </ul>	<ul style="list-style-type: none"> <li>• Cement/Sand render</li> <li>• Underfloor Heated Screeds</li> <li>• Concrete Brick/Block</li> <li>• Electric Underfloor Heating</li> <li>• Vinyl Tiles/Sheets</li> <li>• Fibre cement sheets</li> <li>• Flooring grade Asphalt &amp; Bitumen</li> </ul>	<ul style="list-style-type: none"> <li>• Porcelain</li> <li>• Ceramics</li> <li>• Terracotta</li> <li>• Quarry</li> <li>• Natural Stones</li> <li>• Mosaics</li> <li>• Composite</li> <li>• Quartz</li> </ul>

<b>Water Addition:</b>	Approximately 5 litres of water to 20kg Setaflex
<b>Coverage:</b>	20kg will cover 5 – 6m <sup>2</sup> at 3mm thin bed application
<b>Pot Life at 20°C:</b>	Approximately 30 minutes
<b>Grout After:</b>	3 hours
<b>Colours:</b>	Grey & White
<b>Pack Sizes:</b>	5kg, 10kg & 20kg packs
<b>Specification Category:</b>	Conforms to BS EN 12004 Class C2 FT S1