



DECLARATION OF PERFORMANCE No 015

1. Unique identification code of the product-type: **ULTIMATE**
2. Intended use/es: **Improved fast setting cementitious adhesive for all internal and external tiling**
3. Manufacturer: **Tilemaster Adhesives Ltd - Kerakoll Group - Tomlinson Road, Leyland, Lancashire, PR25 2DY, UK.**
4. System/s of AVCP:
System 3
System 4 for reaction to fire
5. Harmonised standard: **EN 12004:2007 + A1:2012**
Notified body/ies: **CERAM Research Ltd No. 1289**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class F
Bond strength as: early tensile adhesion strength initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$
Durability for: Tensile adhesion strength after heat ageing Tensile adhesion strength after water immersion Tensile adhesion strength after freeze-thaw cycles	$\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Filippo Iacconi (General Manager)**

At Leyland, on 28/07/2020

www.tilemasteradhesives.co.uk - www.kerakoll.com

Tilemaster Adhesives Ltd - Kerakoll Group – Tomlinson Road, Leyland, Lancashire, PR25 2DY, United Kingdom

Tel. 01772 456 831 – e-mail: info@tilemasteradhesives.co.uk – Company Registration n° 04627336

VAT number GB 636237732